



whittle

WAXES

FOR BEAUTIFUL TIMBER
NATURALLY...

Product Information

Treatex Traditional Hardwax Oil

Description: Durable clear hardwax finish that is easily maintained, is water repellent and dirt resistant, will not discolour, crack, flake or peel, safe for use on children's toys contains no pollutants and minimal solvents. Allows timber to breathe and move seasonally, enhances natural grain and timber colour, is non yellowing and will not edge bond when applied correctly. With a proper application process Hardwax Oil will not flake, blister or peel. Available in a range of colours and four sheen levels, Matte, Luster, Satin, and Gloss.

Areas of use: For the coating of all internal timber, particularly floors, as well as porous surfaces such as stone tiles.

Floor Preparation: The floor needs to have been well sanded to a 120 grit Screen. Vacuum the surface thoroughly to remove all dirt and dust. Before applying Treatex® to the whole floor, please test on a small area. Plan how you are going to coat the floor in an efficient manner. Stir tin thoroughly and pour required amount to complete the coat into paint tray.

Application: Buff the floor with a Maroon Scotch-brite pad or 200 grit screen. Vacuum the surface thoroughly to remove all dirt and dust. Apply Treatex® cutting in from skirtings using the brush, do not get too far ahead. Load the roller from the paint tray and apply an even coat of Treatex® to the floor. Work the length of the boards covering an area approximately 750mm in width. Work efficiently and aim to achieve an even coat.

Coverage If you are using the optional Treatex®, you should achieve with the 1st coat 15-20m²/L and with the 2nd coat ~25m²/L.

Clean tools: Use *Whittle Waxes Special Thinner* to clean rollers and brushes.

Drying Time: Allow to dry for at least 12 hrs – Warmth and ventilation will speed up the drying process. Cold and humidity may slow down the process.

Storage: Indefinitely in sealed container.

Ingredients: Oil and Wax combinations on a base of natural, sustainable raw materials including Linseed oil, sunflower oil, Jojoba oil, Beeswax, carnauba wax and candalilla wax.

Colours: Spruce, Ebony, Mahogany, Medium Oak, Dark Oak

Container sizes: 500ml, 1L, 2.5L, 5L,

Although our products are natural and ecological please;

- Keep out of reach of children. May cause allergic reactions.
- Completely empty containers before recycling.
- Dried waste material can be disposed of as household waste or construction waste.
- Liquid disposed of at paint collection facility.
- In case of contact with the skin, rinse immediately with clear water.
- It must not be allowed to escape into the sewage system or in flowing water.

Disclaimer: Our technical advice in written form is given in good faith and on the basis of experiments, but it is only non-binding advice and does not release you from the obligation to test the products supplied by us as to their suitability for the particular purpose. Application, use and processing of the products outside our direct control are entirely your responsibility. Naturally we guarantee consistent quality of our products corresponding to the original sample. With release of new product information the previous information loses validity.

Whittle Waxes Victoria 6/9 Pilgrim Court Ringwood VIC 3134 Ph: 03 9873 8484
1300 ECOWAX (1300 326 929) info@whittlewaxes.com.au www.whittlewaxes.com.au